United States Patent [19]

Lauenstein et al.

[11] **Patent Number: 4,932,423**

[45] **Date of Patent: Jun. 12, 1990**

[54] **TOBACCO FEEDING APPARATUS**

[75] Inventors: **Michael Lauenstein**, Cormondrèche; **Bernard Tallier**, Gorgier, both of Switzerland

[73] Assignee: **Fabriques de Tabac Reunies, S.A.**, Neuchatel, Switzerland

[21] Appl. No.: **268,989**

[22] Filed: **Nov. 9, 1988**

[30] **Foreign Application Priority Data**

Nov. 16, 1987 [CH] Switzerland 4450/87

[51] **Int. Cl.**[5] **A24C 5/39**

[52] **U.S. Cl.** **131/110**; 131/108; 131/109.1; 131/109.2; 131/84.3

[58] **Field of Search** 131/110, 108, 109.1, 131/109.2, 84.1, 84.3

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,544,167	12/1970	Fuchu et al.	131/110
3,580,644	5/1971	Ballard	131/110
4,832,058	5/1989	Labbe	131/110

FOREIGN PATENT DOCUMENTS

2139870 11/1984 United Kingdom

Primary Examiner—V. Millin
Assistant Examiner—Jennifer L. Doyle
Attorney, Agent, or Firm—Jeffrey H. Ingerman

[57] **ABSTRACT**

In apparatus for feeding tobacco to cigarette-making machines, the tobacco (9) is conveyed by suction from a feed receptacle (1). One end (14) of a duct (3) facing the receptacle above the level (19) of the tobacco is provided with a device (16) for regulating the rate of tobacco delivery in order to allow continuous feeding of the cigarette-making machine. The regulating device comprises a movable sleeve (17) slidable on the end portion (14) of the duct so that the bottom rim (18) of the sleeve is always at a required distance H from the level of the tobacco, this distance being continuously detected by a sensor (25), and the quantity of tobacco drawn into the duct to be adapted to the rate of production being a function of H. The other end (15) of the duct opens out into a tangential separator (12). The regulating device combined with the tangential separator makes it possible to reduce damage to the particles of tobacco.

8 Claims, 3 Drawing Sheets



2026230387

Source: https://www.industrydocuments.ucsf.edu/docs/jfjl0000